



## UV FLASH DRY 15/700

Code no. 999

- // Designed for spot repair
- // Time savings of up to 70 % compared to conventional IR drying
- // Higher through put in your body shop
- // Press and hold simultaneously two push buttons starts the UV curing process
- // Low heating of the coated surface
- // Highest load capacity of electronics and flash tube
- // Aluminium drawn cased housing with metal sides
- // Off-grid operation in combination with Hensel Power Max L (optional accessory)

### TECHNICAL DATA

Irradiance<sup>1</sup>: UV 200 - 400 nm 369 mJ/m<sup>2</sup> per flash

Drying area: approx. 25 cm x 25 cm

Time for UV curing: 30 s

Stored energy: 1500 J

Flash tube, plug-in style, lifetime<sup>2</sup> 250,000 flashes

Input voltage: 230 V

Quick change automatic for reflector

Weight: approx. 25.0 kg

Overall dimensions (LxBxH): 66 x 55 x 105 cm

<sup>1</sup> Measured with a calibrated spectrometer with a distance of 0.5 m

<sup>2</sup> Reduction of the spectral intensity by 20 %

Technical data are subject to change. The listed values are guide values and should not be understood as binding in a legal sense.

The values can differ due to tolerances in used components.

Values attained at 230 V / 50 Hz voltage. Date of revision: March 2014

**VISIT**  
■■■■ INDUSTRIAL LIGHT