



## EH PRO 3000

Code no. 3599

- // Sturdy housing in 2.6 mm aluminum drawn profile
- // Bright 650 W modeling light
- // Plug-in safety dome
- // Plug-in flash tube
- // Active cooling with quiet fan
- // Up to 3000 Ws performance
- // Large selection of quickly changeable Hensel EH light formers
- // Utmost stability for reflectors and accessories
- // Stable flash cable inlet at the head
- // 5 m flash cable with low inner resistance for maximum performance
- // Multivoltage (90 V - 240 V)

### TECHNICAL DATA

- Output: 3000 J
- Connection: 20-pin plug
- Modeling lamp up to: 650 W
- Cooling fan: Yes
- Reflector connection: EH (10 cm)
- Cable length: 5 m
- Multivoltage: Yes
- On/off switch for flash and modeling lamp: Yes
- Pluggable flash tube: Yes
- Glass dome: Yes
- Integrated umbrella holder with clamp: Yes
- Weight (incl. 5 m cable): 3.1 kg
- Dimensions (LxWxH): 24.5 x 15 x 23 cm (without cable)

Technical data are subject to change. The listed values are guide values and should not be understood as binding in a legal sense.

The values can differ due to tolerances in used components.

Values attained at 230 V / 50 Hz voltage. Date of revision: October 2013

**HENSEL**  
■■■■ PERFORMING LIGHT